



GRAND LIGHTING™

GL300 Gen II LED Projector

Encased in an IP65 enclosure this fully weatherised fixture is perfect for your outdoor installation.

The high quality optical system produces a crisp vivid gobo image and the flat field gives you a crystal clear projection right to the edge.

All come with your choice of fixed lens to suit your location and built in gobo rotation that can be easily turned on or off using the front facia button.

FEATURES

- High quality optical system offers sharp image quality
- Standard Lens Available:
 - F140 Narrow Lens
 - F15 Wide Lens
- Fully weatherised IP65 rated fixture suitable for outdoor installation
- Rear cooling fins and waterproof fan protected by 1.5mm mesh
- Utilising a 300W CREE LED Array. Protected in the IP65 enclosure
- Image rotation function comes as standard. This feature can easily be turned on or off using the front facia button
- Quiet operation making it suitable for indoor use
- 66mm gobo size
- Cool white LED as standard
- Supplied with Meanwell Constant Current Low Voltage Power Supply.

Use only with supplied PSU

DIMENSIONS

- Length (excluding lens): 370mm
- Width (with knobs) : 250mm
- Body Height: 180mm
- Height (with base): 320mm
- Weight: 9kg
- External Power Supply IP65 Meanwell HLG-320H-36A: 252mm x 90mm x 44mm
- Input Voltage: 100-240V AC
- Average Power Consumption: 280Watts

PHOTOMETRICS



	GL300 Gen II	F140 NARROW LENS		
Projection Diameter (m)	1.58m	3.17m	4.75m	6.34m
Luminance (lux)	3553 lux	888 lux	395 lux	222 lux
Projection Distance (m)	5m	10m	15m	20m

	GL300 Gen II	F115 WIDE LENS		
Projection Diameter (m)	2.03m	4.07m	6.10m	8.14m
Luminance (lux)	2615 lux	654 lux	291 lux	163 lux
Projection Distance (m)	5m	10m	15m	20m

*LUX values indicated are not peak values, which may be higher.
We give average LUX readings taken under actual tests.*

PHYSICAL DIMENSIONS

